

Model : ATZ NET-PP24-C6A-110-SH

Description: Cat6A 19" 1U 24 Ports Shielded Patch Panel
Krone/110 type



This 19" 1U 24-ports rack mountable CAT6A patch panel is a great solution for network and cable management adopting colour coded 110/Krone termination blocks. It offers a clearly labelled, neat and effective cable organisation for speed and efficiency, ideal for the heart of any centralized network. Our patch panels meet and exceeds industry standards, ensuring secure and optimal network performance.

Features:

- Every port is shielded & 100% tested to ensure NEXT and return loss performance
- individually serialized to support traceability;
- Utilizes 110 punchdown termination on back panel and includes retention cap for each port;
- Each port contains a universal label that is color coded for T568A and T568B wiring schemes;
- Terminates 4 pair, 22 - 26 AWG, 100 ohm, solid or stranded twisted pair cable;

pg. 1

Notes: - All brand names and trademarks are properties of their respective holders and are referred to here for descriptive purpose only. Photo attached is for reference only, it may be slightly varied in items of colour, shape from the actual item delivered from time to time.

All specifications are subject to change without prior notice.
© Copyright ATZ

Model : ATZ NET-PP24-C6A-110-SH

Description: Cat6A 19" 1U 24 Ports Shielded Patch Panel
Krone/110 type

- Used for standard EIA 19" rack

Specifications:

Material	
Panel	1.2mm/ Steel Powder coated cold rolled (Shielded type)
RJ45 Housing	Polycarbonate High-Impact UL94V-0
RJ45 Contact	Phosphor Bronze with 50-60µ" Nickel plated
	Contact area 3-50µ" Gold plated
IDC Housing	Cold-rolled steel + Polycarbonate, erosion resistance powder coating High-Impact UL94V-0
IDC Terminal	Phosphor Bronze with 50µ" Tin-Lead plated. Over 50-60µ" Nickel plated.
	Use for 22-26 AWG stranded and solid wire
Jack bracket set	ABS Black colour
PCB	FR4 UL94V-0
Performance	
The IDC wiring type	T568A & T568B
Insertion Force	900g for 8 contacts
Retention Strength	7.7kg between Jack & Plug
Operation Temp	-40°C to 70°C
Durability	Jack: 750 cycles Plug-Jack mating and unmating test (ISO/IEC 11801, IEC 60603-7-4)
	IDC: Max 200 punching times.
General	
Net weight:	13kg
Length:	19" 24-port
Height	1U

Model : ATZ NET-PP24-C6A-110-SH
Description: Cat6A 19" 1U 24 Ports Shielded Patch Panel
 Krone/110 type

Product Diagram:

