

Model : ATZ VC-HDMI-V2-HDMI+eARC

Description: HDMI v2.0 4K@60 18Gbps ARC/eARC Audio Adapter







This 4K HDMI ARC/eARC Audio Adapter is capable to output Dolby Atmos audio from an external HDMI source to eARC/ARC sound systems. Since compliant with audio formats such as LPCM, Dolby True HD and DTS-HD Master Audio, this adapter is a perfect solution for connecting SONOS ARC/BOSE 500/BOSE 700 Soundbars and other eARC/ARC audio/video receivers. It also provides a dedicated HDMI output port for outputting audio only when connecting with legacy AVR without eARC/ARC function.



Model : ATZ VC-HDMI-V2-HDMI+eARC

Description: HDMI v2.0 4K@60 18Gbps ARC/eARC Audio Adapter

Features:

- HDMI 2.0b and HDCP 2.3 compliant
- Support 18Gbps video bandwidth
- Support video resolution up to 4K2K@60Hz with 24-bit RGB/YCbCr 4:4:4
- Support HDR, HDR10, HDR10+, Dolby Vision and HLG pass through
- Support HDMI audio formats: LPCM, Dolby Digital/Plus/EX, Dolby TrueHD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DSD
- Perfect solution for SONOS ARC/BOSE 500/BOSE 700 Soundbars and other eARC/ARC audio/video receivers
- Dedicated HDMI port for outputting audio only when connecting with legacy AVR without eARC/ARC function
- Built-in Equalizer, Retiming and Driver
- Auto EDID management
- Compact design for easy and flexible installation

Specifications:

| Technical | | |
|--------------------|--|--|
| HDMI Compliance | HDMI 2.0b | |
| HDCP Compliance | HDCP 2.3 | |
| Video Bandwidth | 18Gbps | |
| Video Resolution | Up to 4K2K@60Hz with 24-bit RGB/YCbCr 4:4:4 | |
| Color Depth | 8-bit,10-bit,12-bit | |
| Color Space | RGB, YCbCr_4:4:4, YCbCr_4:2:2, YCbCr_4:2:0 | |
| HDMI Audio Formats | LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DSD | |
| Connection | | |
| Input | 1×HDMI IN [Type A, 19-pin female] | |
| Output | 1×HDMI SOUND BAR [Type A, 19-pin female] 2×HDMI OUT [Type A, 19-pin female] | |
| Control | 1×SERVICE [Micro USB, Update port] | |
| Mechanical | | |
| Housing | Metal Enclosure | |
| Silkscreen Color | Black | |
| Dimensions | 120mm (W) × 70mm (D) × 16mm (H) | |
| Weight | 210g | |
| Power Supply | DC 5V/1A | |




Model : ATZ VC-HDMI-V2-HDMI+eARC


Description: HDMI v2.0 4K@60 18Gbps ARC/eARC Audio Adapter

| Power Consumption | 2.28W (Max) |
|---------------------|-----------------------------|
| Operation | 200 4000 / 2005 40405 |
| Temperature | 0°C ~ 40°C / 32°F ~ 104°F |
| Storage Temperature | -20°C ~ 60°C / -4°F ~ 140°F |
| Relative Humidity | 20~90% RH (non-condensing) |

Operation Controls and Functions Front Panel



Rear Panel



| No. | Name | Function Description |
|-----|------------------|--|
| 1 | POWER LED | When the device is powered on, the red LED will light on. |
| 2 | HDMI IN LED | When the HDMI IN port connects with a signal source, the green LED will light on. |
| 3 | HDMI OUT1 LED | When the HDMI OUT1 port connects with a display, the green LED will light on. |
| 4 | HDMI OUT2 LED | When the HDMI OUT2 port connects with a display, the green LED will light on. |
| 5 | ARC/eARC LED | When the ARC/eARC function is turned on, the green LED will light on. |
| 6 | ARC/eARC button | Press this button, the ARC/eARC function will be enabled; Press it once again, the function will be disabled. |
| 7 | SERVICE port | Firmware update port. |
| 8 | HDMI IN | HDMI signal input port, connect to a HDMI source device such as DVD or PS5 with the HDMI cable. |
| 9 | SOUND BAR | ARC/eARC-capable audio signal output port, connect to a Soundbar with the HDMI cable. |
| 10 | HDMI OUT1 | ARC/eARC-capable HDMI signal output port, connect to a TV with ARC/eARC function. |
| 11 | HDMI OUT2 | Dedicated audio signal output port, connect to an Amplifier or TV. When connecting to a TV set, it will output audio only with black screen. |
| 12 | DC 5V | DC 5V Power input port. |



Model : ATZ VC-HDMI-V2-HDMI+eARC

Description: HDMI v2.0 4K@60 18Gbps ARC/eARC Audio Adapter


Package Includes:

1× 4K HDMI ARC/eARC Audio Adapter

1x 5V/1A American Standard Power Adaptor

1x User Manual

Product Diagram:



Warranty: 2 years

Warranty is effective from the date of original delivery.

This warranty shall be void if a serial number has been removed from the product.

HDMI^{*}

The terms HDMI and HDMI High-Definition Multimedia interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.